NSN 5910-00-057-0348

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-057-0348 **Body Style:** Piston **Bushing Diameter:** 0.255 inches **Shaft Diameter:** 0.112 inches single shaft **Bushing Length:** 0.250 inches **Shaft Length:** 0.297 inches single shaft **Body Length:** 0.438 inches **Overall Diameter:** 0.310 inches Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -50.0/+50.0 single section **Mounting Facility Screw Thread Series Designator:** Unf **Inclosure Type:** Encapsulated **Bushing Shape:** Round w/flat Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms **Bushing Width:** 0.234 inches **Mounting Facility Type And Quantity:** 1 threaded bushing **Nonderated Operating Temp:** Between -55.0 degrees celsius and 150.0 degrees celsius **Thread Size:** 0.250 inches Shaft Type: Round, slotted single shaft Capacitance Range In Picofarads: +0.7/+4.5 single section **Nonderated Voltage Rating And Type:** 1000.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 shaft

Test Data Document:

38597-6269-3 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

NSN 5910-00-057-0348

Glass Dielectric Variable Capacitor - Page 2 of 2



Terminal Type And Quantity:
1 ferrule
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A096a0