NSN 5910-00-057-5200

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-057-5200					
Body Style:					
W/mtg bracket, axial terminals					
Reliability Indicator:					
Not established					
Terminal Length:					
0.296 inches					
Body Diameter:					
0.670 inches					
Body Length:					
1.875 inches					
Unthreaded Mounting Hole Diameter:					
0.156 inches					
Schematic Diagram Designator:					
No common or grounded electrode (s)					
Mounting Facility Type And Quantity:					
1 unthreaded mounting holes					
Features Provided:					
Hermetically sealed case					
Insulation Resistance At Maximum Operating Temp:					
5.0 megohm-microfarads					
Capacitance Value Per Section:					
0.470 microfarads single section					
Nonderated Operating Temp:					
Between -55.0 degrees celsius and 125.0 degrees celsius					
Nonderated Continuous Voltage Rating And Type Per Section:					
600.0 dc single section					
Tolerance Range Per Section:					
-10.00/+10.00 percent single section					
Case Material:					
Metal					
Insulation Resistance At Reference Temp:					
2000.0 megohm-microfarads					
Power Factor At Reference Tempurature In Percent:					
1.5000					
Terminal Surface Treatment:					
Solder					
Case Insulation Material:					
Plastic					
Terminal Type And Quantity:					
2 tab, solder lug					
Shelf Life:					

N/a

NSN 5910-00-057-5200

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



ш	Inıt	· / 1+	Measure	

--

Demilitarization:

No

Fiig:

A010b0