## NSN 5910-00-059-1038

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-059-1038

view Online at https://aerobasegroup.com/nsn/5910-00-059-1036
Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Length:
0.500 inches
Body Width:
0.090 inches
Body Height:
0.500 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
1280.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
-2400.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-400.0/+400.0 single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Ceramic
Insulation Resistance At Reference Temp:
100000.0 megohms
Power Factor At Reference Tempurature In Percent:
0.2000
Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Test Data Document:
13499-9uo-4981 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)

N/a

Shelf Life:

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-00-059-1038

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



	• •					
ın	18	<i>(</i> )+	Me	20	III	ω.

--

Demilitarization:

No

Fiig:

A010b0