NSN 5910-00-059-4191

Glass Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-059-4191

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.000 inches
Body Length:
0.391 inches
Body Width:
0.109 inches
Body Height:
0.203 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
2.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
140.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
500.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-25.0 to 25.0 single section
Criticality Code Justification:
Test
Tolerance Range Per Section:
-0.75 to 0.75 picofarads single section
Case Material:
Glass
Dissipation Factor At Reference Tempurature In Percent:
0.1000
Terminal Surface Treatment:
Solder
Test Data Document:
94756-441-0340 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 uninsulated wire lead

--

N/a

Shelf Life:

Unit Of Measure:

NSN 5910-00-059-4191

Glass Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0