Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-060-1967

# **Body Style:**

W/o mtg facilities, terminal (s) on one end

# **Reliability Indicator:**

Not established

# **Body Diameter:**

1.375 inches

#### **Body Length:**

2.750 inches

#### Schematic Diagram Designator:

One terminal common to each section

# Anode Type:

Plain foil

# Impedance At Minimum Operating Tempurature In Ohms:

350.0

# **Electrical Polarization:**

# Polarized

Section Quantity:

3

# Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

# **Tolerance Range Per Section:**

-10.00 to 50.00 percent 3rd section

#### Case Material:

Metal

#### **Capacitive Electrode Material:**

Aluminum

#### Dc Leakage At Reference Temp:

140.000 microamperes

# **Terminal Surface Treatment:**

Solder

# **Test Data Document:**

81349-mil-c-62 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

4 tab, solder lug

# **Specification Data:**

81349-mil-c-62/5 government specification

#### Shelf Life:

N/a

#### Unit Of Measure:

---

Demilitarization:

No

# NSN 5910-00-060-1967

Electrolytic Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

