NSN 5910-00-060-2422

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-060-2422

Body Style:
W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end
Reliability Indicator:
Not establishednot established
Body Diameter:
1.000 inches
Body Length:
2.000 inches
Terminal Diameter:
0.109 inches
Terminal Height From Body:
0.470 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Plain foil
Electrical Polarization:
Polarized
Mounting Facility Screw Thread Series Designator:
Unc
Mounting Facility Type And Quantity:
2 threaded mounting holes
Capacitance Value Per Section:
1100.000 microfarads single section
Nonderated Operating Temp:
Between -20.0 degrees celsius and 85.0 degrees celsius
Thread Size:
0.138 inches
Nonderated Continuous Voltage Rating And Type Per Section:
10.0 dc single section
Tolerance Range Per Section:
-10.00/+100.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Tempurature In Ohms:

0.25

Dc Leakage At Reference Temp:

1.100 milliamperes

Terminal Surface Treatment:

Solder

NSN 5910-00-060-2422

Electrolytic Fixed Capacitor - Page 2 of 2



Case Insulation Material:
Plastic
Terminal Type And Quantity:
2 standoff, solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0