NSN 5910-00-061-2606

Electrolytic Fixed Capacitor - Page 1 of 2



view Online at https://aerobasegroup.com/hsh/5910-00-061-2606
Body Style:
W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals
Reliability Indicator:
Not establishednot established
Terminal Length:
1.500 inches 1.500 inches 1.500 inches
Body Diameter:
0.135 inches
Body Length:
0.286 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Anode Type:
Solid
Electrical Polarization:
Polarized
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
0.560 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 65.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
35.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Tantalum
Dc Leakage At Reference Temp:
1.000 microamperes
Terminal Surface Treatment:
Solder
Test Data Document:
81349-mil-c-26655 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:

N/a

2 uninsulated wire lead

Unit Of Measure:

Shelf Life:

NSN 5910-00-061-2606

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0