NSN 5910-00-061-5266

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-061-5266
Body Style:
W/mtg bracket, axial terminals
Reliability Indicator:
Not established
Terminal Length:
1.625 inches
Body Diameter:
0.400 inches
Body Length:
1.312 inches
Body Width:
0.852 inches
Body Height:
0.478 inches
Terminal Diameter:
0.032 inches
Unthreaded Mounting Hole Diameter:
0.144 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Internal Electrical Connection Type:
Extended foil
Mounting Facility Type And Quantity:
1 unthreaded mounting holes
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
150.0 megohms
Capacitance Value Per Section:
47000.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
600.0 dc single section
Tolerance Range Per Section:
-10.00 to 10.00 percent single section
Case Material:
Metal
Institution Designation of At Defending Towns

Insulation Resistance At Reference Temp:

18000.0 megohms

Terminal Surface Treatment:

Solder

NSN 5910-00-061-5266

Paper Dielectric Fixed Capacitor - Page 2 of 2



Test Data Document:

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-25/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0