

View Online at <https://aerobasegroup.com/nsn/5910-00-062-6664>

**Body Style:**

W/thd bushing mtg, terminals on opposite ends

**Reliability Indicator:**

Not established

**Body Diameter:**

0.562 inches

**Body Length:**

1.375 inches

**Continuous Current Rating In Amps:**

10.0

**Schematic Diagram Designator:**

Feedthrough

**Mounting Facility Screw Thread Series Designator:**

Unf

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Features Provided:**

Hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:**

10.0 megohm-microfarads

**Capacitance Value Per Section:**

0.100 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Thread Size:**

0.312 inches

**Nonderated Continuous Voltage Rating And Type Per Section:**

600.0 dc single section

**Tolerance Range Per Section:**

-10.00 to 10.00 percent single section

**Case Material:**

Metal

**Insulation Resistance At Reference Temp:**

18000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

1.0000

**Test Data Document:**

81349-mil-c-11693/7 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 uninsulated wire lead w/terminal lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0