

View Online at <https://aerobasegroup.com/nsn/5910-00-062-6966>

Body Style:

W/thd mtg hol (s)/stud(s) terminal(s) on one surface

Reliability Indicator:

Not established

Body Length:

1.500 inches

Body Width:

1.656 inches

Body Height:

3.500 inches

Center To Center Distance Between Terminals Parallel To Width:

1.062 inches

Terminal Height From Body:

0.875 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.093 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Mounting Facility Type And Quantity:

2 threaded mounting studs

Features Provided:

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

20.0 megohm-microfarads

Capacitance Value Per Section:

2.500 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

250.0 dc single section

Tolerance Range Per Section:

-15.00 to 15.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

Dissipation Factor At Reference Temperature In Percent:

1.0000

Terminal Surface Treatment:

Solder

Test Data Document:

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 wire hook/loop

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0