NSN 5910-00-063-6458

Electrolytic Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-063-6458

| Body Style: | |
|---|----|
| W/twist tab mtg, terminal (s) on one endw/twist tab mtg, terminal(s) on one endw/twist tab mtg, | าด |
| Reliability Indicator: | |
| Not establishednot established | |
| Body Diameter: | |
| 1.469 inches | |
| Body Length: | |
| 2.000 inches | |
| Schematic Diagram Designator: | |
| Electrod (s) grounded to case | |
| Anode Type: | |
| Plain foil | |
| Electrical Polarization: | |
| Polarized | |
| Capacitance Value Per Section: | |
| 2000.000 microfarads single section | |
| Nonderated Operating Temp: | |
| Between -20.0 degrees celsius and 85.0 degrees celsius | |
| Nonderated Continuous Voltage Rating And Type Per Section: | |
| 20.0 dc single section | |
| Tolerance Range Per Section: | |
| -10.00/+150.00 percent single section | |
| Case Material: | |
| Metal | |
| Capacitive Electrode Material: | |
| Aluminum | |
| Terminal Surface Treatment: | |
| Solder | |
| Terminal Type And Quantity: | |
| 1 tab, solder lug | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A010b0 | |