

View Online at https://aerobasegroup.com/nsn/5910-00-064-2359

Reliability Indicator: Not established Terminal Length: 1.120 inches Body Length: 0.797 inches Body Height: 0.797 inches Insulation Resistance At Maximum Operating Temp: 7.5 megohm-microfarads Unable To Decode: Between -55.0 degrees celsius and unable to decode Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section 7.2.00 to 2.00 percent single section Case Material: Plastic Solder Solder Solder Insul of Measure: Demilitarization: No Fig: A010b0		
Terminal Length:1.120 inchesBody Length:0.797 inchesBody Height:0.797 inchesInsulation Resistance At Maximum Operating Temp:7.5 megohm-microfaradsUnable To Decode:Between -55.0 degrees celsius and unable to decodeNonderated Continuous Voltage Rating And Type Per Section:300.0 dc single sectionTolerance Range Per Section:-2.00 to 2.00 percent single sectionCase Material:PlasticSolderShelf Life:N/aUnit Of Measure:-Demilitarization:NoFiig:	Reliability Indicator:	
1.120 inches Body Length: 0.797 inches Body Height: 0.797 inches Insulation Resistance At Maximum Operating Temp: 7.5 megohm-microfarads Unable To Decode: Between -55.0 degrees celsius and unable to decode Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -2.00 to 2.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established	
Body Length: 0.797 inches Body Height: 0.797 inches Insulation Resistance At Maximum Operating Temp: 7.5 megohm-microfarads Unable To Decode: Between -55.0 degrees celsius and unable to decode Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -2.00 to 2.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Shelf Life: N/a Unit Of Measure: Demilitarization: No	Terminal Length:	
0.797 inches Body Height: 0.797 inches Insulation Resistance At Maximum Operating Temp: 7.5 megohm-microfarads Unable To Decode: Between -55.0 degrees celsius and unable to decode Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -2.00 to 2.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	1.120 inches	
Body Height: 0.797 inches Insulation Resistance At Maximum Operating Temp: 7.5 megohm-microfarads Unable To Decode: Between -55.0 degrees celsius and unable to decode Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -2.00 to 2.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Shelf Life: N/a Unit Of Measure: Demilitarization: No	Body Length:	
0.797 inches Insulation Resistance At Maximum Operating Temp: 7.5 megohm-microfarads Unable To Decode: Between -55.0 degrees celsius and unable to decode Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -2.00 to 2.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Shelf Life: N/a Unit Of Measure: - Demilitarization: No	0.797 inches	
Insulation Resistance At Maximum Operating Temp: 7.5 megohm-microfarads Unable To Decode: Between -55.0 degrees celsius and unable to decode Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -2.00 to 2.00 percent single section Case Material: Plastic Plastic Terminal Surface Treatment: Solder Shelf Life: N/a Unit Of Measure: Demilitarization: No	Body Height:	
7.5 megohm-microfarads Unable To Decode: Between -55.0 degrees celsius and unable to decode Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -2.00 to 2.00 percent single section Case Material: Plastic Plastic Plastic Terminal Surface Treatment: Solder Shelf Life: N/a Dint Of Measure: Pomilitarization: No	0.797 inches	
Unable To Decode: Between -55.0 degrees celsius and unable to decode Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -2.00 to 2.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Sheff Life: N/a Unit Of Measure: No Fig:	Insulation Resistance At Maximum Operating Temp:	
Between -55.0 degrees celsius and unable to decode Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -2.00 to 2.00 percent single section Case Material: Plastic Plastic Terminal Surface Treatment: Solder Shelf Life: N/a Unit Of Measure: Demilitarization: No	7.5 megohm-microfarads	
Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tolerance Range Per Section: -2.00 to 2.00 percent single section Case Material: Plastic Plastic Terminal Surface Treatment: Solder Shelf Life: N/a Unit Of Measure: Demilitarization: No	Unable To Decode:	
300.0 dc single section Tolerance Range Per Section: -2.00 to 2.00 percent single section Case Material: Plastic Plastic Terminal Surface Treatment: Solder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between -55.0 degrees celsius and unable to decode	
Tolerance Range Per Section: -2.00 to 2.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Solder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Nonderated Continuous Voltage Rating And Type Per Section:	
-2.00 to 2.00 percent single section Case Material: Plastic Terminal Surface Treatment: Solder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	300.0 dc single section	
Case Material: Plastic Plastic Terminal Surface Treatment: Solder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Tolerance Range Per Section:	
Plastic Terminal Surface Treatment: Solder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-2.00 to 2.00 percent single section	
Terminal Surface Treatment: Solder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Case Material:	
Solder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Plastic	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Surface Treatment:	
N/a Unit Of Measure: Demilitarization: No Fiig:	Solder	
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:	
 Demilitarization: No Fiig:	N/a	
Demilitarization: No Fiig:	Unit Of Measure:	
No Fiig:	-	
Fiig:	Demilitarization:	
•	No	
A010b0	Fiig:	
	A010b0	