

View Online at https://aerobasegroup.com/nsn/5910-00-064-2919

### **Body Style:**

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.250 inches

**Body Length:** 

0.500 inches

**Body Width:** 

0.500 inches

**Body Height:** 

0.187 inches

#### Center To Center Distance Between Terminals Parallel To Length:

Between 0.347 inches and 0.407 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Capacitance Value Per Section:**

1.000 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

#### Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

#### **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

#### **Case Material:**

Plastic

#### Insulation Resistance At Reference Temp:

2500.0 megohm-microfarads

#### **Dissipation Factor At Reference Tempurature In Percent:**

4.0000

#### **Terminal Surface Treatment:**

Solder

# Test Data Document:

36378-452666 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5910-00-064-2919 Ceramic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

