NSN 5910-00-064-8033

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-064-8033

Bodv	Styl	۰.
DOUV	Jινι	e.

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

Reliability Indicator:

Not establishednot established

Terminal Length:

1.250 inches 1.250 inches 1.250 inches

Body Diameter:

0.390 inches

Body Length:

0.969 inches

Terminal Diameter:

0.032 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Etched foil

Impedance At Minimum Operating Tempurature In Ohms:

110.0

Electrical Polarization:

Polarized

Capacitance Value Per Section:

18.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

11.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

60.0 dc single section

Tolerance Range Per Section:

-10.00/+75.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Tempurature In Ohms:

125 00

Dc Leakage At Reference Temp:

3.500 microamperes

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

NSN 5910-00-064-8033

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Type Ar	nd Quantity:
------------------	--------------

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0