

View Online at <https://aerobasegroup.com/nsn/5910-00-067-5646>

Body Style:

Piston

Overall Length:

Between 1.149 inches and 1.211 inches

Terminal Length:

0.500 inches

Body Length:

Between 0.969 inches and 1.031 inches

Overall Diameter:

0.313 inches

Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Center To Center Distance Between Terminals Parallel To Length:

Between 0.844 inches and 0.906 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.281 inches

Terminal Diameter:

Between 0.025 inches and 0.035 inches

Quality Factor At 25 Deg Celsius:

500.0

Fragility Factor:

Moderately rugged

Inclosure Type:

Encapsulated

Adjustment Device Torque:

Between 1.000 inch-ounces and 10.000 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

1000000.0 megohms

Mounting Facility Type And Quantity:

4 terminal

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Capacitance Range In Picofarads:

+0.8 to 18.0 single section

Nonderated Voltage Rating And Type:

750.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.04 single section

Material:

Glass inclosure

Precious Material And Location:

Stator silver

Precious Material:

Silver

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0