## NSN 5910-00-067-6707

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-067-6707

**Body Style:** 

W/thd bushing mtg, terminals on opposite ends

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.296 inches

**Body Diameter:** 

0.670 inches

**Body Length:** 

1.562 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Mounting Facility Screw Thread Series Designator:** 

Unf

**Mounting Facility Type And Quantity:** 

1 threaded bushing

**Features Provided:** 

Hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:** 

40000.0 megohm-microfarads

**Capacitance Value Per Section:** 

0.100 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.313 inches

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-120.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

**Tolerance Range Per Section:** 

-10.00/+10.00 percent single section

**Case Material:** 

Metal

Insulation Resistance At Reference Temp:

250000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

0.1000

**Dielectric Material:** 

Plastic

## NSN 5910-00-067-6707

Plastic Dielectric Fixed Capacitor - Page 2 of 2



<b>Ferminal</b>	Type	And	Quantity:
-----------------	------	-----	-----------

2 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0