

View Online at <https://aerobasegroup.com/nsn/5910-00-068-4424>

**Body Style:**

W/o mtg facilities, axial terminals w/o mtg facilities, axial terminals

**Reliability Indicator:**

Not established not established

**Terminal Length:**

2.000 inches 2.000 inches

**Body Diameter:**

0.375 inches

**Body Length:**

1.500 inches

**Schematic Diagram Designator:**

Electrod (s) grounded to case, w/gnd terminal

**Anode Type:**

Plain foil

**Impedance At Minimum Operating Temperature In Ohms:**

590.0

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

18.000 microfarads single section

**Nonderated Operating Temp:**

Between -40.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

100.0 dc single section

**Tolerance Range Per Section:**

-10.00/+75.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Dissipation Factor At Reference Temperature In Percent:**

15.0000

**Dc Leakage At Reference Temp:**

9.400 microamperes

**Terminal Surface Treatment:**

Solder

**Test Data Document:**

81349-mil-c-62 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0