## NSN 5910-00-068-9093

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-068-9093

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Length:
0.570 inches
Body Width:
0.170 inches
Body Height:
0.290 inches
Terminal Diameter:
0.020 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
47000.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
ggg.
100.0 dc single section
100.0 dc single section
100.0 dc single section  Tolerance Range Per Section:
100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section
100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material:
100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic
100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic  Insulation Resistance At Reference Temp:
100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic  Insulation Resistance At Reference Temp: 250.0 megohm-microfarads
100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 250.0 megohm-microfarads  Terminal Surface Treatment:
100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic  Insulation Resistance At Reference Temp: 250.0 megohm-microfarads  Terminal Surface Treatment: Solder
100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 250.0 megohm-microfarads  Terminal Surface Treatment: Solder  Terminal Type And Quantity:
100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 250.0 megohm-microfarads  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead
100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 250.0 megohm-microfarads  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life:
100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 250.0 megohm-microfarads  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a
100.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 250.0 megohm-microfarads  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a
Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 250.0 megohm-microfarads  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a Unit Of Measure:
Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 250.0 megohm-microfarads Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: