

View Online at <https://aerobasegroup.com/nsn/5910-00-069-0267>

**Body Style:**

W/thd bushing mtg, terminal (s) on one endw/thd bushing mtg, terminal(s) on one endw/thd bushing mtg, terminal(s) on one end

**Reliability Indicator:**

Not establishednot establishednot established

**Body Diameter:**

1.375 inches

**Body Length:**

2.750 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Etched foil

**Impedance At Minimum Operating Temperature In Ohms:**

8.0

**Electrical Polarization:**

Polarized

**Mounting Facility Screw Thread Series Designator:**

Un

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Features Provided:**

Mounting hardware

**Capacitance Value Per Section:**

100.000 microfarads single section

**Nonderated Operating Temp:**

Between -40.0 degrees celsius and 85.0 degrees celsius

**Thread Size:**

0.875 inches

**Nonderated Continuous Voltage Rating And Type Per Section:**

200.0 dc single section

**Tolerance Range Per Section:**

-10.00/+50.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Power Factor At Reference Temperature In Percent:**

12.0000

**Dc Leakage At Reference Temp:**

210.000 microamperes

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0