

View Online at <https://aerobasegroup.com/nsn/5910-00-069-0267>

Body Style:

W/thd bushing mtg, terminal (s) on one endw/thd bushing mtg, terminal(s) on one endw/thd bushing mtg, terminal(s) on one end

Reliability Indicator:

Not establishednot establishednot established

Body Diameter:

1.375 inches

Body Length:

2.750 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Etched foil

Impedance At Minimum Operating Temperature In Ohms:

8.0

Electrical Polarization:

Polarized

Mounting Facility Screw Thread Series Designator:

Un

Mounting Facility Type And Quantity:

1 threaded bushing

Features Provided:

Mounting hardware

Capacitance Value Per Section:

100.000 microfarads single section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.875 inches

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

Tolerance Range Per Section:

-10.00/+50.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Power Factor At Reference Temperature In Percent:

12.0000

Dc Leakage At Reference Temp:

210.000 microamperes

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0