## NSN 5910-00-069-6876

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-069-6876

Bodv	Styl	۰.
DOUV	Jινι	e.

W/o mtg facilities terminal (s) on one surfacew/o mtg facilities terminal(s) on one surfacew/o mtg facilities terminal(s) on one surfacew/o mtg facilities terminal(s)

## **Reliability Indicator:**

Not establishednot established

**Terminal Length:** 

1.500 inches 1.500 inches 1.500 inches

**Body Length:** 

0.600 inches

**Body Width:** 

0.375 inches

**Body Height:** 

0.195 inches

Center To Center Distance Between Terminals Parallel To Length:

0.500 inches

**Terminal Diameter:** 

0.032 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Anode Type:** 

Solid

**Electrical Polarization:** 

Polarized

**Capacitance Value Per Section:** 

22.000 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+10.00 percent single section

**Case Material:** 

Plastic

**Capacitive Electrode Material:** 

Tantalum

**Dissipation Factor At Reference Tempurature In Percent:** 

6.0000

Dc Leakage At Reference Temp:

3.000 microamperes

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-00-069-6876

Electrolytic Fixed Capacitor - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0