NSN 5910-00-069-9845

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-069-9845

| Body Style: |
|--|
| W/thd mtg hole/stud, terminal (s) on one endw/thd mtg hole/stud, terminal(s) on one endw/thd mtg hole/stud, ter |
| Reliability Indicator: |
| Not establishednot established |
| Terminal Length: |
| 2.500 inches 2.500 inches 2.500 inches |
| Body Diameter: |
| 0.750 inches |
| Body Length: |
| 1.375 inches |
| Terminal Diameter: |
| 0.032 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Anode Type: |
| Plain foil |
| Electrical Polarization: |
| Nonpolarized |
| Mounting Facility Screw Thread Series Designator: |
| Unc |
| Mounting Facility Type And Quantity: |
| 1 threaded mounting studs |
| Capacitance Value Per Section: |
| 0.100 microfarads single section |
| Nonderated Operating Temp: |
| Between -40.0 degrees celsius and 65.0 degrees celsius |
| Thread Size: |
| 0.112 inches |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 1500.0 dc single section |
| Tolerance Range Per Section: |
| -20.00/+20.00 percent single section |
| Case Material: |
| Metal |
| Capacitive Electrode Material: |
| Aluminum |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |

N/a

Shelf Life:

2 uninsulated wire lead

NSN 5910-00-069-9845

Electrolytic Fixed Capacitor - Page 2 of 2



| | | eas | |
|--|--|-----|--|

--

Demilitarization:

No

Fiig:

A010b0