NSN 5910-00-070-2417



Electrolytic Fixed Capacitor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5910-00-070-2417
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
1.250 inches
Body Diameter:
0.391 inches
Body Length:
0.781 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Anode Type:
Solid
Electrical Polarization:
Polarized
Capacitance Value Per Section:
150.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Dc Leakage At Maximum Operating Temp:
24.0 milliamperes
Nonderated Continuous Voltage Rating And Type Per Section:
20.0 dc single section
Tolerance Range Per Section:
-10.00 to 10.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Tantalum
Equivalent Series Resistance At Reference Tempurature In Ohms:
4.00
Dc Leakage At Reference Temp:
4.000 microamperes
Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Test Data Document:
94580-479511 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-00-070-2417

Electrolytic Fixed Capacitor - Page 2 of 2



Shelf	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0