

View Online at <https://aerobasegroup.com/nsn/5910-00-070-8044>

**Body Style:**

W/twist tab mtg, terminal (s) on one endw/twist tab mtg, terminal(s) on one endw/twist tab mtg, terminal(s) on one end

**Reliability Indicator:**

Not establishednot establishednot established

**Terminal Length:**

0.312 inches 0.312 inches 0.312 inches

**Body Diameter:**

1.000 inches

**Body Length:**

2.500 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Plain foil

**Impedance At Minimum Operating Tempurature In Ohms:**

148.0

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

60.000 microfarads single section

**Nonderated Operating Temp:**

Between -40.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

250.0 dc single section

**Tolerance Range Per Section:**

-10.00/+125.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Dissipation Factor At Reference Tempurature In Percent:**

0.1700

**Dc Leakage At Reference Temp:**

0.100 microamperes

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0