

View Online at <https://aerobasegroup.com/nsn/5910-00-071-7533>

Body Style:

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

Reliability Indicator:

Not establishednot establishednot established

Terminal Length:

Between 1.500 inches and 1.500 inches and 1.500 inches and 2.500 inches 2.500 inches 2.500 inches

Body Diameter:

Between 0.297 inches and 0.327 inches

Body Length:

Between 0.781 inches and 0.843 inches

Terminal Diameter:

0.032 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Anode Type:

Plain foil

Electrical Polarization:

Polarized

Capacitance Value Per Section:

150.000 microfarads single section

Nonderated Operating Temp:

Between -20.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

3.0 dc single section

Tolerance Range Per Section:

-10.00/+75.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Dc Leakage At Reference Temp:

1.200 microamperes

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0