## NSN 5910-00-075-7532

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-075-7532

**Body Style:** 

W/mtg tabs/flanges, terminal (s) on one surface

Reliability Indicator:

Not established

**Mounting Slot Width:** 

0.213 inches

**Body Length:** 

Between 3.719 inches and 3.781 inches

**Body Width:** 

Between 2.219 inches and 2.281 inches

**Body Height:** 

Between 4.469 inches and 4.531 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 1.938 inches and 2.062 inches

**Terminal Height From Body:** 

1.125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.375 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

**Mounting Facility Type And Quantity:** 

4 mounting slots

**Features Provided:** 

Hermetically sealed case

**Capacitance Value Per Section:** 

10.000 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

2000.0 dc single section

**Tolerance Range Per Section:** 

-20.00 to 20.00 percent single section

**Case Material:** 

Metal

Insulation Resistance At Reference Temp:

10000.0 megohm-microfarads

**Terminal Type And Quantity:** 

2 threaded stud

Shelf Life:

N/a

## NSN 5910-00-075-7532

Plastic Dielectric Fixed Capacitor - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A010b0