## NSN 5910-00-079-0073

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-079-0073

W/o mtg facilities, axial terminals  Reliability Indicator:  Not established  Terminal Length:  1.625 inches  Body Diameter:  0.313 inches  Body Length:  0.750 inches  Terminal Diameter:  0.032 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section:  0.200 microfarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  200.0 dc single section  Tolerance Range Per Section:  -10.00/+10.00 percent single section  Case Material:  Plastic  Dissipation Factor At Reference Tempurature In Percent:  1.5000  Terminal Surface Treatment:  Solder  Terminal Type And Quantity:  2 uninsulated wire lead  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Body Style:
Not established  Terminal Length: 1.625 inches Body Diameter: 0.313 inches Body Length: 0.750 inches  Terminal Diameter: 0.032 inches  Schematic Diagram Designator: No common or grounded electrode (s)  Capacitance Value Per Section: 0.200 microfarads single section  Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.5000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fiig:	W/o mtg facilities, axial terminals
Terminal Length:  1.625 inches  Body Diameter:  0.313 inches  Body Length:  0.750 inches  Terminal Diameter:  0.032 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section:  0.200 microfarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  200.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material:  Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.5000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Reliability Indicator:
Body Diameter:  0.313 inches Body Length: 0.750 inches Terminal Diameter: 0.032 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 0.200 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Dissipation Factor At Reference Tempurature In Percent: 1.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Not established
Body Diameter:  0.313 inches Body Length: 0.750 inches Terminal Diameter: 0.032 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 0.200 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Dissipation Factor At Reference Tempurature In Percent: 1.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Length:
0.313 inches  Body Length: 0.750 inches  Terminal Diameter: 0.032 inches  Schematic Diagram Designator: No common or grounded electrode (s)  Capacitance Value Per Section: 0.200 microfarads single section  Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.5000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	1.625 inches
Body Length: 0.750 inches Terminal Diameter: 0.032 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 0.200 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Dissipation Factor At Reference Tempurature In Percent: 1.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Diameter:
O.750 inches Terminal Diameter: O.032 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: O.200 microfarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Dissipation Factor At Reference Tempurature In Percent: 1.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.313 inches
Terminal Diameter:  0.032 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section:  0.200 microfarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  200.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material:  Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.5000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Body Length:
O.032 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section:  0.200 microfarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  200.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material:  Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.5000  Terminal Surface Treatment:  Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	0.750 inches
Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section:  0.200 microfarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  200.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material:  Plastic  Dissipation Factor At Reference Tempurature In Percent:  1.5000  Terminal Surface Treatment:  Solder  Terminal Type And Quantity:  2 uninsulated wire lead  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Terminal Diameter:
No common or grounded electrode (s)  Capacitance Value Per Section: 0.200 microfarads single section  Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.5000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	0.032 inches
Capacitance Value Per Section:  0.200 microfarads single section  Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.5000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Schematic Diagram Designator:
0.200 microfarads single section  Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.5000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	No common or grounded electrode (s)
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  200.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material:  Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.5000  Terminal Surface Treatment:  Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	Capacitance Value Per Section:
Between -55.0 degrees celsius and 85.0 degrees celsius  Nonderated Continuous Voltage Rating And Type Per Section:  200.0 dc single section  Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.5000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	0.200 microfarads single section
Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Dissipation Factor At Reference Tempurature In Percent: 1.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Nonderated Operating Temp:
Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.5000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Between -55.0 degrees celsius and 85.0 degrees celsius
Tolerance Range Per Section: -10.00/+10.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.5000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Nonderated Continuous Voltage Rating And Type Per Section:
-10.00/+10.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.5000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	200.0 dc single section
Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 1.5000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fiig:	Tolerance Range Per Section:
Plastic  Dissipation Factor At Reference Tempurature In Percent:  1.5000  Terminal Surface Treatment:  Solder  Terminal Type And Quantity:  2 uninsulated wire lead  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	-10.00/+10.00 percent single section
Dissipation Factor At Reference Tempurature In Percent:  1.5000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Case Material:
1.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Plastic
Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Dissipation Factor At Reference Tempurature In Percent:
Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1.5000
Terminal Type And Quantity:  2 uninsulated wire lead  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Terminal Surface Treatment:
2 uninsulated wire lead  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Solder
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No Fiig:	2 uninsulated wire lead
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A010b0	Fiig:
A010b0	A010b0