# NSN 5910-00-079-6823

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-079-6823

| Bodv | Styl | ۰. |
|------|------|----|
| DOUV | Jινι | e. |

W/o mtg facilities, terminal (s) on one endw/o mtg facilities, terminal(s) on one endw/o mtg facilities, terminal(s) on one end

#### **Reliability Indicator:**

Not establishednot established

## **Terminal Length:**

0.062 inches 0.062 inches 0.062 inches

### **Body Diameter:**

1.375 inches

#### **Body Length:**

4.125 inches

#### **Center To Center Distance Between Terminals Parallel To Diameter:**

1.250 inches

## **Terminal Diameter:**

0.190 inches

#### **Schematic Diagram Designator:**

Electrod (s) grounded to case, w/gnd terminal

## **Anode Type:**

Etched foil

#### **Electrical Polarization:**

Polarized

## **Capacitance Value Per Section:**

6500.000 microfarads single section

#### **Nonderated Operating Temp:**

Between -40.0 degrees celsius and 85.0 degrees celsius

## Dc Leakage At Maximum Operating Temp:

4.05 milliamperes

## Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+100.00 percent single section

#### **Case Material:**

Metal

## **Capacitive Electrode Material:**

Aluminum

## **Equivalent Series Resistance At Reference Tempurature In Ohms:**

0.071

#### **Case Insulation Material:**

Plastic

## **Terminal Type And Quantity:**

2 threaded hole

## Shelf Life:

N/a

# NSN 5910-00-079-6823

Electrolytic Fixed Capacitor - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0