## NSN 5910-00-080-2407

Ceramic Dielectric Variable Capacitor - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5910-00-080-2407  |
|--|
| Body Style:  |
| Rotary   |
| Overall Length:  |
| 0.750 inches   |
| Overall Height:  |
| 0.234 inches   |
| Overall Width:   |
| 0.531 inches   |
| Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: |
| -750.0 single section  |
| Quality Factor At 25 Deg Celsius:                              |
| 500.0  |
| Inclosure Type:  |
| Encased  |
| Adjustment Device Torque:                                      |
| Between 2.000 inch-ounces and 8.000 inch-ounces                |
| Mounting Facility Type And Quantity:                           |
| 2 terminal   |
| Nonderated Operating Temp:                                     |
| Between -55.0 degrees celsius and 85.0 degrees celsius         |
| Capacitance Range In Picofarads:                               |
| +8.0 to 50.0 single section                                    |
| Nonderated Voltage Rating And Type:                            |
| 350.0 dc continuous single section                             |
| Adjustment Device Drive Type And Quantity:                     |
| 1 slotted screw  |
| Terminal Type And Quantity:                                    |
| 2 tab, solder lug  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A096a0   |
|  |