

View Online at <https://aerobasegroup.com/nsn/5910-00-080-7413>

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Not established

Terminal Length:

1.500 inches

Body Diameter:

0.160 inches

Body Length:

0.240 inches

Terminal Diameter:

0.028 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Arleigh burke class ddg; ticonderoga class cg (47); forrestal class cv; los angeles clas (688); spruance class dd (963) ; helicopter, advance attack, ah-1w; kidd class ddg; helicopter, mh-53e; nimitz class cvn

Capacitance Value Per Section:

8.200 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

1000.0 megohms

Power Factor At Reference Temperature In Percent:

1.0000

Terminal Surface Treatment:

Solder

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0