

View Online at https://aerobasegroup.com/nsn/5910-00-080-9561

### **Body Style:**

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.250 inches

Body Length:

0.290 inches

Body Width:

0.290 inches

**Body Height:** 

0.090 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.185 inches and 0.215 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

#### Capacitance Value Per Section:

6800.000 picofarads single section

## Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-66.0/+22.0 with rated voltage applied single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 150.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### Insulation Resistance At Reference Temp:

100000.0 megohms

Power Factor At Reference Tempurature In Percent:

2.5000

**Terminal Surface Treatment:** 

Solder

#### **Test Data Document:**

81349-mil-c-11015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

# NSN 5910-00-080-9561 Ceramic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

