## NSN 5910-00-082-4704



Plastic Dielectric Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-082-4704 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 0.143 inches **Body Length:** 0.700 inches **Body Width:** 0.360 inches **Body Height:** 0.220 inches Center To Center Distance Between Terminals Parallel To Length: Between 0.405 inches and 0.495 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **Insulation Resistance At Maximum Operating Temp:** 1000.0 megohm-microfarads **Capacitance Value Per Section:** 75000.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 10000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 0.3200 **Terminal Surface Treatment:** Solder Plastic polyethylene terephthalate

**Dielectric Material: Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a

## NSN 5910-00-082-4704

Plastic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0