

View Online at https://aerobasegroup.com/nsn/5910-00-085-2717

### **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.250 inches

### **Body Diameter:**

0.225 inches

**Body Length:** 

0.540 inches

**Terminal Diameter:** 

0.032 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Capacitance Value Per Section:**

100.000 picofarads single section

## Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-15.0/+15.0 with rated voltage applied single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

### **Tolerance Range Per Section:**

-20.00 to 20.00 percent single section

**Case Material:** 

Ceramic

Insulation Resistance At Reference Temp:

20000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

1.5000

**Terminal Surface Treatment:** 

Solder

# Test Data Document:

81349-mil-c-11015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

2 uninsulated wire lead

### **Specification Data:**

81349-mil-c-11015/1c government specification

Shelf Life:

N/a

- Unit Of Measure:
- --



Demilitarization:

No

Fiig:

A010b0