NSN 5910-00-086-2760

Not establishednot established

Body Style:

Reliability Indicator:

3 uninsulated wire lead

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-086-2760

W/mtg bracket, axial terminalsw/mtg bracket, axial terminalsw/mtg bracket, axial terminals

| Terminal Length: |
|--|
| 2.500 inches 2.500 inches 2.500 inches |
| Body Diameter: |
| 0.875 inches |
| Body Length: |
| 1.812 inches |
| Terminal Diameter: |
| 0.040 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.156 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Anode Type: |
| Solid |
| Electrical Polarization: |
| Nonpolarized |
| Mounting Facility Type And Quantity: |
| 1 unthreaded mounting holes |
| Section Quantity: |
| 2 |
| Capacitance Value Per Section: |
| 30.000 microfarads all sections |
| Nonderated Operating Temp: |
| Between -20.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 150.0 dc all sections |
| Tolerance Range Per Section: |
| -10.00/+50.00 percent all sections |
| Case Material: |
| Metal |
| Capacitive Electrode Material: |
| Aluminum |
| Dissipation Factor At Reference Tempurature In Percent: |
| 15.0000 |
| Case Insulation Material: |
| Plastic |
| Terminal Type And Quantity: |

NSN 5910-00-086-2760

Electrolytic Fixed Capacitor - Page 2 of 2



| _ | | | | |
|---|----|------|---|------|
| c | hο | JIF. | | ife: |
| J | | | _ | HG. |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0