Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-086-8568

## **Body Style:**

W/thd mtg studs, terminal (s) on the end

**Reliability Indicator:** 

Not established

## **Terminal Length:**

1.625 inches

#### **Body Diameter:**

0.562 inches

#### **Body Length:**

1.875 inches

### Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.125 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

### Mounting Facility Screw Thread Series Designator:

Unc

### Mounting Facility Type And Quantity:

2 threaded mounting studs

### **Features Provided:**

Hermetically sealed case

### Insulation Resistance At Maximum Operating Temp:

100.0 megohm-microfarads

## Capacitance Value Per Section:

2.000 microfarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

#### Thread Size:

0.138 inches

### Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

#### **Case Material:**

Metal

### Insulation Resistance At Reference Temp:

50000.0 megohm-microfarads

### **Dissipation Factor At Reference Tempurature In Percent:**

1.0000

## **Dielectric Material:**

Plastic polyethylene terephthalate

# Terminal Type And Quantity:

2 uninsulated wire lead

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0