NSN 5910-00-086-8568

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-086-8568					
Body Style:					
W/thd mtg studs, terminal (s) on the end					
Reliability Indicator:					
Not established					
Terminal Length:					
1.625 inches					
Body Diameter:					
0.562 inches					
Body Length:					
1.875 inches					
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:					
1.125 inches					
Schematic Diagram Designator:					
No common or grounded electrode (s)					
Mounting Facility Screw Thread Series Designator:					
Unc					
Mounting Facility Type And Quantity:					
2 threaded mounting studs					
Features Provided:					
Hermetically sealed case					
Insulation Resistance At Maximum Operating Temp:					
100.0 megohm-microfarads					
Capacitance Value Per Section:					
2.000 microfarads single section					
Nonderated Operating Temp:					
Between -55.0 degrees celsius and 85.0 degrees celsius					
Thread Size:					
0.138 inches					
Nonderated Continuous Voltage Rating And Type Per Section:					

400.0 dc single section

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

50000.0 megohm-microfarads

Dissipation Factor At Reference Tempurature In Percent:

1.0000

Dielectric Material:

Plastic polyethylene terephthalate

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-00-086-8568

Plastic Dielectric Fixed Capacitor - Page 2 of 2



SI	1e	lf	Ιi	fe:
Ο.	···	•••	_	٠٠.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0