## NSN 5910-00-088-1710

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-088-1710
Body Style:
W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals
Reliability Indicator:
Establishedestablished
Terminal Length:
1.500 inches 1.500 inches 1.500 inches
Body Diameter:
0.289 inches
Body Length:
0.686 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Anode Type:
Solid
Electrical Polarization:
Polarized
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
68.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 65.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
15.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Tantalum
Dc Leakage At Reference Temp:
20.000 microamperes
Terminal Surface Treatment:
Solder
Test Data Document:
81349-mil-c-26655 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

N/a

Shelf Life:

**Unit Of Measure:** 

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-00-088-1710

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0