NSN 5910-00-089-4429

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-089-4429

Body Style:

Piston

Overall Length:

2.327 inches

Terminal Length:

0.500 inches

Body Length:

Between 2.234 inches and 2.296 inches

Overall Diameter:

Between 0.187 inches and 0.249 inches

Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:

-50.0 single section

Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:

-150.0 to 150.0 single section

Center To Center Distance Between Terminals Parallel To Length:

Between 2.187 inches and 2.249 inches

Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.218 inches and 0.250 inches

Terminal Diameter:

0.031 inches

Center To Center Distance Between Mounting Facilities Parallel To Diameter:

Between 0.218 inches and 0.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.187 inches and 2.249 inches

Quality Factor At 25 Deg Celsius:

500.0

Inclosure Type:

Encased

Adjustment Device Torque:

Between 1.000 inch-ounces and 10.000 inch-ounces

Insulation Dc Resistance At Max Operating Temp:

100000.0 megohms

Mounting Facility Type And Quantity:

4 terminal

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Capacitance Range In Picofarads:

+50.0 to 300.0 single section

Nonderated Voltage Rating And Type:

125.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

NSN 5910-00-089-4429

Glass Dielectric Variable Capacitor - Page 2 of 2



Terminal Type And Quantity:
4 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A096a0