

View Online at https://aerobasegroup.com/nsn/5910-00-089-9927

#### **Body Style:**

W/mtg bracket, axial terminals

**Reliability Indicator:** 

Not established

## **Terminal Length:**

0.297 inches

#### **Body Diameter:**

0.562 inches

#### **Body Length:**

1.375 inches

### **Unthreaded Mounting Hole Diameter:**

0.156 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### Internal Electrical Connection Type:

Inserted tab

#### Mounting Facility Type And Quantity:

1 unthreaded mounting holes

#### **Features Provided:**

Hermetically sealed case

### Insulation Resistance At Maximum Operating Temp:

10.0 megohm-microfarads

### Capacitance Value Per Section:

68000.000 picofarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

1000.0 dc single section

### **Tolerance Range Per Section:**

-10.00 to 10.00 percent single section

#### **Case Material:**

Metal

## Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

# Power Factor At Reference Tempurature In Percent:

1.0000

# **Terminal Surface Treatment:**

Solder

# Terminal Type And Quantity:

2 tab, solder lug

## Shelf Life:

N/a

Paper Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0