NSN 5910-00-100-8133

Mica Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/psn/5910-00-100-8133

| View Online at https://aerobasegroup.com/nsn/5910-00-100-8133 |
|--|
| Body Style: |
| W/o mtg facilities, terminals on opposite surfaces |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.125 inches |
| Body Length: |
| 0.734 inches |
| Body Width: |
| 0.187 inches |
| Body Height: |
| 0.437 inches |
| Terminal Diameter: |
| 0.032 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Insulation Resistance At Maximum Operating Temp: |
| 15000.0 megohms |
| Capacitance Value Per Section: |
| 390.000 picofarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 500.0 dc single section |
| Tolerance Range Per Section: |
| -5.00 to 5.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 100000.0 megohms |
| Quality Factor At Reference Temp: |
| 1.000 |
| Terminal Surface Treatment: |
| Solder |
| Test Data Document: |
| 81349-mil-c-5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |

2 uninsulated wire lead

Specification Data:

81349-mil-c-5/2a government specification

Shelf Life:

N/a

NSN 5910-00-100-8133

Mica Dielectric Fixed Capacitor - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0