NSN 5910-00-101-2642

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-101-2642

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Not established

Terminal Length:

Between 1.250 inches and 1.750 inches

Body Diameter:

0.219 inches

Body Length:

0.578 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Anode Type:

Solid

Impedance At Minimum Operating Tempurature In Ohms:

250.0

Electrical Polarization:

Polarized

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

10.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

2.0 milliamperes

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Range Per Section:

-20.00 to 20.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Power Factor At Reference Tempurature In Percent:

6 0000

Equivalent Series Resistance At Reference Tempurature In Ohms:

8.00

Dc Leakage At Reference Temp:

1.000 microamperes

Terminal Surface Treatment:

Solder

NSN 5910-00-101-2642 Electrolytic Fixed Capacitor - Page 2 of 2



Case insulation Material:
Plastic
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0