

View Online at <https://aerobasegroup.com/nsn/5910-00-101-4917>

Body Style:

W/mtg tabs/flanges, terminal (s) on one surface

Reliability Indicator:

Not established

Body Length:

2.281 inches

Body Width:

1.266 inches

Body Height:

1.781 inches

Maximum Rf Current Rating At Highest Rated Frequency In Rms Amps:

13.0

Highest Frequency At Which Rf Current Rating Applies In Kilohertz:

3000.0

Maximum Rf Current Rating At Lowest Rated Frequency In Rms Amps:

6.2

Lowest Frequency At Which Rf Current Rating Applies In Kilohertz:

100.0

Unthreaded Mounting Hole Diameter:

0.180 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.625 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Mounting Facility Type And Quantity:

1 unthreaded mounting holes

Capacitance Value Per Section:

20000.000 picofarads single section

Nonderated Continuous Voltage Rating And Type Per Section:

2000.0 ac-peak single section

Tolerance Range Per Section:

-5.00 to 5.00 percent single section

Case Material:

Plastic

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0