## NSN 5910-00-102-9162

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-102-9162

| Bodv | Styl | ۰. |
|------|------|----|
| DOUV | Jινι | e. |

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not establishednot established

**Terminal Length:** 

1.500 inches 1.500 inches 1.500 inches

**Body Diameter:** 

0.279 inches

**Body Length:** 

0.650 inches

**Schematic Diagram Designator:** 

Electrod (s) grounded to case, w/gnd terminal

**Anode Type:** 

Solid

**Electrical Polarization:** 

Polarized

**Features Provided:** 

Hermetically sealed case

**Capacitance Value Per Section:** 

6.800 microfarads single section

**Nonderated Operating Temp:** 

Between -80.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+10.00 percent single section

Case Material:

Metal

**Capacitive Electrode Material:** 

**Tantalum** 

**Dissipation Factor At Reference Tempurature In Percent:** 

6.0000

Dc Leakage At Reference Temp:

6.000 microamperes

**Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

Plastic

**Test Data Document:** 

03640-6099393 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-00-102-9162

Electrolytic Fixed Capacitor - Page 2 of 2



| _  |   |   |    |    |    |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
|    |   |   |    |    |    |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0