## NSN 5910-00-103-3837

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-103-3837

	Body Style:					
	W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals					
Reliability Indicator:						
	Not establishednot established					
	Terminal Length:					
	2.500 inches 2.500 inches 2.500 inches					
	Body Diameter:					
	0.562 inches					
	Body Length:					
	2.250 inches					
	Terminal Diameter:					
	0.032 inches					
	Schematic Diagram Designator:					
	Electrod (s) grounded to case, w/gnd terminal					
	Anode Type:					
	Plain foil					
	Electrical Polarization:					
	Polarized					
	Capacitance Value Per Section:					
	40.000 microfarads single section					
	Nonderated Operating Temp:					
	Between -20.0 degrees celsius and 85.0 degrees celsius					
	Dc Leakage At Maximum Operating Temp:					
	5.0 milliamperes					
	Nonderated Continuous Voltage Rating And Type Per Section:					
	150.0 dc single section					
	Tolerance Range Per Section:					
	-10.00/+50.00 percent single section					
	Case Material:					
	Metal					
	Capacitive Electrode Material:					
	Aluminum					
	Dissipation Factor At Reference Tempurature In Percent:					
	18.0000					

Dc Leakage At Reference Temp:

1.000 milliamperes

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

## NSN 5910-00-103-3837

Electrolytic Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0