NSN 5910-00-103-4250

Mica Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-103-4250 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.0100 **Terminal Length:** 1.000 inches **Body Length:** Between 0.400 inches and 0.460 inches **Body Width:** 0.370 inches **Body Height:** Between 0.095 inches and 0.180 inches **Center To Center Distance Between Terminals Parallel To Length:** 0.225 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 10000.0 megohms **Capacitance Value Per Section:** 130.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: +0.0 to 70.0 single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 100000.0 megohms **Terminal Surface Treatment:** Solder Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5910-00-103-4250

Mica Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0