Mica Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-103-4250

## Body Style:

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.0100

**Terminal Length:** 

1.000 inches

**Body Length:** 

Between 0.400 inches and 0.460 inches

**Body Width:** 

0.370 inches

**Body Height:** 

Between 0.095 inches and 0.180 inches

Center To Center Distance Between Terminals Parallel To Length:

0.225 inches

**Terminal Diameter:** 

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Insulation Resistance At Maximum Operating Temp:

10000.0 megohms

Capacitance Value Per Section:

130.000 picofarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

#### Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius:

+0.0 to 70.0 single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

100000.0 megohms

**Terminal Surface Treatment:** 

Solder

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

# NSN 5910-00-103-4250

Mica Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

