NSN 5910-00-103-7527

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-103-7527

| D - | ٠. د | C4 | ٠ |
|------------|------|-----|-----|
| DU | uv | Stv | ıe: |

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

Reliability Indicator:

Not establishednot established

Terminal Length:

Between 1.750 inches and 1.750 inches and 2.250 inches 2.250 inches

Body Diameter:

Between 0.303 inches and 0.323 inches

Body Length:

Between 0.740 inches and 0.760 inches

Terminal Diameter:

0.032 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Etched foil

Electrical Polarization:

Polarized

Capacitance Value Per Section:

35.000 microfarads single section

Nonderated Operating Temp:

Between -30.0 degrees celsius and 50.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

15.0 dc single section

Tolerance Range Per Section:

-10.00/+100.00 percent single section

Case Material:

Plastic

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Tempurature In Ohms:

11.00

Dc Leakage At Reference Temp:

15.750 microamperes

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5910-00-103-7527

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0