

View Online at <https://aerobasegroup.com/nsn/5910-00-104-1343>

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Not established

Terminal Length:

1.250 inches

Body Diameter:

0.219 inches

Body Length:

0.578 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Solid

Impedance At Minimum Operating Temperature In Ohms:

650.0

Electrical Polarization:

Polarized

Capacitance Value Per Section:

3.500 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

2.0 milliamperes

Nonderated Continuous Voltage Rating And Type Per Section:

75.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Equivalent Series Resistance At Reference Temperature In Ohms:

10.00

Dc Leakage At Reference Temp:

1.000 microamperes

Case Insulation Material:

Plastic

Special Features:

Capacitive electrode material metallic foil

Test Data Document:

81349-mil-c-3965 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0