NSN 5910-00-104-9961

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-104-9961

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Length:
0.400 inches
Body Width:
0.200 inches
Body Height:
0.110 inches
Terminal Diameter:
0.020 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Insulation Resistance At Maximum Operating Temp:
50.0 megohm-microfarads
Capacitance Value Per Section:
2200.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
100.0 dc single section
Tolerance Range Per Section:
-5.00/+5.00 percent single section
Ones Materials
Case Material:
Plastic
Plastic
Plastic Insulation Resistance At Reference Temp:
Plastic Insulation Resistance At Reference Temp: 250.0 megohm-microfarads
Plastic Insulation Resistance At Reference Temp: 250.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent:
Plastic Insulation Resistance At Reference Temp: 250.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.5000
Plastic Insulation Resistance At Reference Temp: 250.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.5000 Terminal Surface Treatment:
Plastic Insulation Resistance At Reference Temp: 250.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.5000 Terminal Surface Treatment: Solder
Plastic Insulation Resistance At Reference Temp: 250.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity:
Plastic Insulation Resistance At Reference Temp: 250.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead
Plastic Insulation Resistance At Reference Temp: 250.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
Plastic Insulation Resistance At Reference Temp: 250.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.5000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a

No

NSN 5910-00-104-9961

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0