

View Online at <https://aerobasegroup.com/nsn/5910-00-105-7522>

Body Style:

W/mtg tabs/flanges, terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

0.750 inches

Body Length:

2.312 inches

Body Width:

2.062 inches

Body Height:

1.125 inches

Center To Center Distance Between Terminals Parallel To Length:

1.062 inches

Unthreaded Mounting Hole Diameter:

0.187 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.375 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Nimitz class cvn; defense support program; yellowstone class ad-41; spruance class dd (963); emory s. Land class as

Mounting Facility Type And Quantity:

2 unthreaded mounting holes

Features Provided:

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

40000.0 megohm-microfarads

Capacitance Value Per Section:

2.000 microfarads single section

Nonderated Operating Temp:

Between -65.0 degrees celsius and 85.0 degrees celsius

Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-120.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Tolerance Range Per Section:

-1.00/+1.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

250000.0 megohm-microfarads

Dissipation Factor At Reference Temperature In Percent:

0.1000

Dielectric Material:

Plastic

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0